

HFC-12

High Flow, 3/8" 通徑

規格 / 材質

- ❖ 工作壓力: 真空至 60psi, 4.2 bar
- ❖ 使用溫度: 0°C 至 71°C
- ❖ 材質: 本體-P.P.
- ❖ 彈簧: 閥/扣門 316 不銹鋼
- ❖ O-Ring: EPDM, 其它材質選用
- ❖ 顏色: 本體/淺灰色, 扣門/灰色

應用例

- ❖ 添充及排水管路
- ❖ 化學品輸送管路
- ❖ 冷卻水管路
- ❖ 相片沖洗化學品
- ❖ 噴霧裝置
- ❖ 廢水處理裝置

◆ 可提供符合美國國家衛生基金會 NSF C-2 規範的接頭

快速接頭母座 Bodies

	編號 (直通)	編號 (附閥)	長度
外牙固定 Rigid Mount			
3/8" NPT	HFC 106-12	HFCD 106-12	2.69"
1/2" NPT	HFC 108-12	HFCD 108-12	2.88"
3/4" NPT	HFC 1012-12	HFCD 1012-12	3.07"
線上連接管鉤接頭 In Line Hose Barb			
3/8" (9.5mm) ID	HFC 176-12	HFCD 176-12	2.79"
1/2" (12.7mm) ID	HFC 178-12	HFCD 178-12	2.79"
5/8" (15.9mm) ID	HFC 1710-12	HFCD 1710-12	2.94"
3/4" (19mm) ID	HFC 1712-12	HFCD 1712-12	2.94"
面板固定管鉤接頭 ★ Panel Mount Hose Barb			
3/8" (9.5mm) ID	HFC 166-12	HFCD 166-12	2.82"
1/2" (12.7mm) ID	HFC 168-12	HFCD 168-12	2.82"
5/8" (15.9mm) ID	HFC 1610-12	HFCD 1610-12	2.94"
3/4" (19mm) ID	HFC 1612-12	HFCD 1612-12	2.94"

★ 面板固定孔直徑: 0.720" ★ 面板厚度: 0.030" 至 0.25"

★ 面板固定孔墊片: EPDM

快速接頭插 Inserts

	編號 (直通)	編號 (附閥)	長度
外牙固定 Rigid Mount			
3/8" NPT	HFC 246-12	HFCD 246-12	1.77"/1.88"
1/2" NPT	HFC 248-12	HFCD 248-12	1.95"/2.06"
3/4" NPT	HFC 2412-12	HFCD 2412-12	2.14"/2.26"
管鉤接頭 Hose Barb			
3/8" (9.5mm) ID	HFC 226-12	HFCD 226-12	1.97"
1/2" (12.7mm) ID	HFC 228-12	HFCD 228-12	1.97"
5/8" (15.8mm) ID	HFC 2210-12	HFCD 2210-12	2.01"
3/4" (19mm) ID	HFC 2212-12	HFCD 2212-12	2.14"
管鉤彎頭 Elbow Hose Barb			
3/8" (9.5mm) ID	HFC 236-12	HFCD 236-12	1.93"/2.05"
1/2" (12.7mm) ID	HFC 238-12	HFCD 238-12	1.97"/2.09"
3/4" (19mm) ID	HFC 2312-12	HFCD 2312-12	1.95"



HFC-35 High Flow, 3/8"通徑

規格 / 材質

- ❖ 工作壓力: 真空至125psi, 8.6 bar
- ❖ 使用溫度: -40°C至137.8°C
- ❖ 材質: 本體-**Polysulfone**
- ❖ 彈簧: 閘扣門316不銹鋼
- ❖ O-Ring: EPDM, 其它材質選用
- ❖ 顏色: 本體/白色, 扣門/灰色

應用例

- ❖ 精密過濾設備
- ❖ 製藥設備
- ❖ 設備的冷卻管路
- ❖ 食品及冷飲設備
- ❖ 生化製程管路
- ❖ 實驗及儀器裝置

◆ 可提供符合美國國家衛生基金會NSF C-2規範的接頭



快速接頭母座 Bodies

	編號 (直通)	編號 (附閘)	長度
外牙固定母座 Rigid Mount			
3/8" NPT	HFC 106-35	HFCD 106-35	2.73"
1/2" NPT	HFC 108-35	HFCD 108-35	2.88"
3/4" NPT	HFC 1012-35	HFCD 1012-35	3.12"
管鉤母座 In Line Hose Barb			
3/8" (9.5mm) ID	HFC 176-35	HFCD 176-35	2.82"
1/2" (12.7mm) ID	HFC 178-35	HFCD 178-35	2.82"
5/8" (15.9mm) ID	HFC 1710-35	HFCD 1710-35	2.94"
3/4" (19mm) ID	HFC 1712-35	HFCD 1712-35	2.94"
面板固定管鉤母座★ Panel Mount Hose Barb			
3/8" (9.5mm) ID	HFC 166-35	HFCD 166-35	2.82"
1/2" (12.7mm) ID	HFC 168-35	HFCD 168-35	2.82"
5/8" (15.9mm) ID	HFC 1610-35	HFCD 1610-35	2.94"
3/4" (19mm) ID	HFC 1612-35	HFCD 1612-35	2.94"

★ 面板固定孔直徑 0.720" ★ 面板厚度: 0.030"至 0.25" ★ 面板固定孔墊片: EPDM



快速接頭插 Inserts

	編號 (直通)	長度	編號 (附閘)	長度
外牙固定(公) Rigid Mount				
3/8" NPT	HFC 246-35	1.82"	HFCD 246-35	1.94"
1/2" NPT	HFC 248-35	1.97"	HFCD 248-35	2.09"
3/4" NPT	HFC 2412-35	2.22"	HFCD 2412-35	2.34"
管鉤接頭(公) Hose Barb				
3/8" (9.5mm) ID	HFC 226-35	1.91"	HFCD 226-35	2.03"
1/2" (12.7mm) ID	HFC 228-35	1.91"	HFCD 228-35	2.03"
5/8" (15.9mm) ID	HFC 2210-35	2.03"	HFCD 2210-35	2.15"
3/4" (19mm) ID	HFC 2212-35	2.03"	HFCD 2212-35	2.15"
管鉤彎頭(公) Elbow Hose Barb				
3/8" (9.5mm) ID	HFC 236-35	1.92"	HFCD 236-35	2.04"
1/2" (12.7mm) ID	HFC 238-35	1.96"	HFCD 238-35	2.16"



HFC-57

High Flow, 3/8" 通徑 ◆抗紫外線適合戶外使用

規格 / 材質

- ❖ 工作壓力: 真空至 125psi, 8.6 bar
- ❖ 使用溫度: -40°C 至 137.8°C
- ❖ 材質: 本體-抗紫外線 Polysulfone
- ❖ 彈簧: 閥扣門 316 不銹鋼
- ❖ O-Ring: EPDM, 其它材質選用
- ❖ 顏色: 本體/扣門-黑色

應用例

- ❖ 農業噴霧設備
- ❖ 投幣販賣設備
- ❖ 化學品輸送管路
- ❖ 水處理設備
- ❖ 動力清洗設備
- 灑水及洗街車



快速接頭母座 Bodies

	編號 (直通)	編號 (附閥)	長度
外牙固定 Rigid Mount			
1/2" NPT	HFC 108-57	HFCD 108-57	2.88"
1/2" BSPT	HFC 108-57 BSPT	HFCD 108-57 BSPT	2.88"
3/8" BSPT	HFC 106-57 BSPT	HFCD 106-57 BSPT	2.73"
3/4" BSPT	HFC 1012-57 BSPT	HFCD 1012-57 BSPT	3.12"
管鉤母座 In Line Hose Barb			
3/8" (9.5mm) ID	HFC 176-57	HFCD 176-57	2.82"
1/2" (12.7mm) ID	HFC 178-57	HFCD 178-57	2.82"
5/8" (15.9mm) ID	HFC 1710-57	HFCD 1710-57	2.94"
3/4" (19mm) ID	HFC 1712-57	HFCD 1712-57	2.94"
面板固定管鉤母座 Panel Mount Hose Barb ★			
3/8" (9.5mm) ID		HFCD 166-57	2.82"
1/2" (12.7mm) ID		HFCD 168-57	2.82"
5/8" (15.9mm) ID		HFCD 1610-57	2.94"
3/4" (19mm) ID		HFCD 1612-57	2.94"



★面板固定孔直徑: 0.720" ★面板厚度: 0.030" 至 0.25" ★面板固定孔墊片: EPDM

快速接頭插 Inserts

	編號 (直通)	編號 (附閥)	長度
外牙固定 Rigid Mount			
1/2" NPT	HFC 248-57	HFCD 248-57	1.95"
3/4" NPT	HFC 2412-57 BSPT	HFCD 2412-57 BSPT	2.19"
管鉤接頭(公) In Line Hose Barb			
3/8" (9.5mm) ID	HFC 226-57	HFCD 226-57	2.03"
1/2" (12.7mm) ID	HFC 228-57	HFCD 228-57	2.03"
5/8" (15.9mm) ID	HFC 2210-57	HFCD 2210-57	2.15"
3/4" (19mm) ID	HFC 2212-57	HFCD 2212-57	2.15"



FFC-35

1/2" 通徑 大流量 Polysulfone 製

規格	應用例	材質
<ul style="list-style-type: none"> ❖ 工作壓力: 真空至 125psi, 8.6 bar ❖ 連續使用溫度: -40°C 至 137.8°C 	<ul style="list-style-type: none"> ❖ 精密過濾設備 ❖ 製藥設備 ❖ 設備的冷卻管路 ❖ 食品及冷飲設備 ❖ 生化製程管路 	<ul style="list-style-type: none"> ❖ 本體/扣門: Polysulfone ❖ O-Ring: 食品級 Buna-N ❖ 彈簧: 316 不銹鋼 ❖ 顏色: 本體白色, 扣門/黑灰 ❖ 墊片: EPDM, 其它材質選



- ❖ 流量加倍外觀尺寸與 HFC 系列一樣
- ❖ 可提供符合美國國家衛生基金會 NSF C-2 規範的接頭

快速接頭母座 Bodies

	編號 (直通)	長度
外牙固定	Rigid Mount	
1/2" NPT	FFC 108-35	2.88"
3/4" NPT	FFC 1012-35	3.12"
管鉤母座	In Line Hose Barb	
3/4" (19mm)	FFC 1712-35	2.94"
面板固定管鉤母座★	Panel Mount Hose Barb	
3/4" (19mm)	FFC 1612-35	2.94"



快速接頭插 Inserts

	編號 (直通)	長度
外牙固定	Rigid Mount	
1/2" NPT	FFC 248-35	1.95"
3/4" NPT	FFC 2412-35	2.14"
管鉤接頭(公)	In Line Hose Barb	
3/4" (19mm)	FFC 2212-35	2.02"



★ 面板固定孔直徑 0.720" ★ 面板厚度: 0.030" 至 0.25" ★ 面板固定孔墊片: EPDM