

Check Valve 止逆(單向)閥

150PSI max., 動作壓力: 1-2PSI, SS316 彈簧, EPDM 密封墊片



編號	規格
2CVF80	1"夾式法蘭連接
2CVF20	2"夾式法蘭連接
2CVF20A	2"全流量夾式法蘭連接
2CVMT8FT8	1" 外牙 x 1 "內牙
2CVFT300	3 "內牙 x 3 "內牙



KYNAR (PVDF)彈簧止逆閥 NPT Male thread SPRING CHECK VALVE

編號	NPT	長度	通徑	工作壓力/溫度:	
CV18PVDF	1/8"	25.40mm	2.38mm	220psi於79.4°C	
CV14PVDF	1/4"	35.71mm	4.76mm	Viton O-Ring	
CV38PVDF	3/8"	38.10mm	6.35mm	NPT外牙	
CV12PVDF	1/2"	46.03mm	8.73mm	止逆動作壓力:1-2.5psi	

Air Actuated Shutoff Pinch Valves PP 氣動閥

型式:常開 NO,動作壓力差 15-20PSI
耐壓力 **70PSI max.** Flow: 50-60 GPM max.
EPDM standard, FKM(Viton)選用



編號	規格
2CS06	3/4" x 3/4"NPT 內牙
2CS80	1" x 1"NPT 內牙
2CS68	1"x 3/4"NPT 內牙



Manifold Pressure Spike Valves 水錘吸收(緩衝)器
FKM(Viton) seal standard,夾式法蘭連接

編號	規格	吸收水壓力
MPRV100-050	1" x 1/2"	50 PSI
MPRV100-075	1" x 3/4"	75 PSI
MPRV100-100	1" x 1"	100 PSI
MPRV100-125	1" x 1 1/4"	125 PSI
MPRV100-150	1" x 1 1/2"	150 PSI

可溶性粉體/液體吸入混合器 PP Inductors (Venturi)



夾式法蘭連接

NPT 外牙

