

# PMC-12 1/8"通徑 P.P.製

規格	應用例	材質
<ul style="list-style-type: none"> <li>❖ 工作壓力: 真空至120 psi, 8.3 bar</li> <li>❖ 連續使用溫度: 0°C 至71°C</li> <li>❖ 可以Gamma射線滅菌</li> </ul>	<ul style="list-style-type: none"> <li>❖ 相片沖洗用化學品</li> <li>❖ 電鍍液</li> <li>❖ 腐蝕性化學品</li> <li>❖ 醫療設備</li> </ul>	<ul style="list-style-type: none"> <li>❖ 本體及閥: P.P.</li> <li>❖ 內彈簧: 316不銹鋼</li> <li>❖ O-Ring: EPDM, 其它材質選用</li> <li>❖ 顏色: 淺土黃色</li> </ul>



## 快速接頭母座 Bodies

螺紋及管徑	編號 (直通)	編號 (附閥)	通徑	長度	
<b>外牙固定 Rigid Mount</b>					
1/8" NPT	PMC 10-02-12	PMCD 10-02-12	1/8"	1.00"	外牙
1/4" NPT	PMC 10-04-12	PMCD 10-04-12	1/8"	1.10"	牙
<b>面板固定 Panel Mount ★</b>					
1.4" x 0.170" (6 x 4.3mm)	PMC 12-04-12	PMCD 12-04-12	1/8"	1.72"	迫緊
<b>線上連接 In Line</b>					
1/16" (1.6mm) ID	PMC 16-01-12	PMCD 16-01-12	1/8"	1.40"	管
1/8" (3.2mm) ID	PMC 16-02-12	PMCD 16-02-12	1/8"	1.65"	
1/4" (6.4mm) ID	PMC 16-04-12	PMCD 16-04-12	1/8"	1.85"	鉤
<b>1/4-28UNF內牙</b>					
面板固定		PMCD 18-042812		1.57"	
線上連接		PMCD 19-042812		1.57"	

- ★ 面板固定孔直徑: PMC 1/2"
- ★ 面板厚度: PMC 0.050" 1/2" max.
- ★ 面板固定螺帽: PMC 5/8" 六角螺帽.



## 快速接頭插 Inserts

螺紋及管徑	編號 (直通)	長度	編號 (附閥)	通徑	長度
<b>外牙固定</b>					
<b>Rigid Mount</b>					
1/8" NPT	PMC 24-02-12	1.03"	PMCD 24-02-12	1/8"	1.45" 外牙
<b>直接頭</b>					
<b>Straight</b>					
1/4" x 0.170" (6 x 4.3mm)	PMC 20-04-12	1.15"	PMCD 20-04-12	1/8"	1.58" 迫緊
1/16" ID	PMC 22-01-12	0.80"	PMCD 22-01-12	1/8"	1.47" 管
1/8" (3.2mm) ID	PMC 22-02-12	1.05"	PMCD 22-02-12	1/8"	1.67"
1/4" (6.4mm) ID	PMC 22-04-12	1.25"	PMCD 22-04-12	1/8"	1.71" 鉤
<b>彎頭</b>					
<b>Elbows</b>					
1/4" x 0.170" (6 x 4.3mm)	-----		PMCD 21-04-12	1/8"	1.21" 迫緊
1/8" (3.2mm) ID	PMC 23-02-12	1.09"	PMCD 23-02-12	1/8"	1.21" 管
1/4" (6.4mm) ID	PMC 23-04-12	1.09"	PMCD 23-04-12	1/8"	1.21" 鉤
<b>1/4-28UNF內牙</b>					
線上連接			PMCD 24042812	1/8"	1.48"
面板固定			PMCD 48042812	1/8"	1.55"



# PLC-12 1/4" 通徑 P.P. 製

## 規格

- ❖ 工作壓力: 真空至 120 psi, 8.3 bar
- ❖ 連續使用溫度: 0°C 至 71°C
- ❖ 可以 Gamma 射線滅菌

## 應用例

- ❖ 相片沖洗用化學品
- ❖ 電鍍液
- ❖ 腐蝕性化學品
- ❖ 醫療設備

## 材質

- ❖ 本體及閥: P.P.
- ❖ 內彈簧: 316不銹鋼
- ❖ O-Ring: EPDM, 其它材質選用
- ❖ 顏色: 淺土黃色



## 快速接頭母座 Bodies

螺紋及管徑	編號 (直通)	編號 (附閥)	通徑	長度	
<b>外牙固定 Rigid Mount</b>					
1/4" NPT	PLC 100-04-12	PLCD 100-04-12	1/4"	1.15"	外牙
3/8" NPT	PLC 100-06-12	PLCD 100-06-12	1/4"	1.15"	外牙
<b>面板固定 Panel Mount ★</b>					
3/8" x 0.250" (9.6 x 6mm)	PLC 120-06-12	PLCD 120-06-12	1/4"	1.95"	迫緊
1/4" (6.4mm) ID	PLC 160-04-12	PLCD 160-04-12	1/4"	1.95"	管
3/8" (9.5mm) ID	PLC 160-06-12	PLCD 160-06-12	1/4"	1.95"	鉤
<b>線上連接 In Line</b>					
3/8" x 0.250" (9.6 x 6mm)	PLC 130-06-12	PLCD 130-06-12	1/4"	1.96"	迫緊
1/4" (6.4mm) ID	PLC 170-04-12	PLCD 170-04-12	1/4"	1.97"	管
3/8" (9.5mm) ID	PLC 170-06-12	PLCD 170-06-12	1/4"	1.97"	鉤
1/4" x 3/8" (6 x 9.5mm)	-----	PLCD 170-406-12	1/4"	2.30"	軟管
3/8" x 1/2" (9.5 x 12.7mm)	-----	PLCD 170-608-12	1/4"	2.36"	迫緊



- ★ 面板固定孔直徑: 1 1/16"
- ★ 面板厚度: 0.020" min. 1/2" max.
- ★ 面板固定螺帽: 3/4" 六角螺帽.



螺紋及管徑	編號 (直通)	長度	編號 (附閥)	通徑	長度	
<b>外牙固定</b>						
<b>Rigid Mount</b>						
1/4" NPT	PLC 240-04-12	1.26"	PLCD 240-04-12	1/4"	1.67"	
<b>面板固定</b>						
<b>Panel Mount ★</b>						
1/4" (6.4mm) ID	PLC 420-04-12	1.91"	PLCD 420-04-12	1/4"	2.05"	管
3/8" (9.5mm) ID	PLC 420-06-12	1.91"	PLCD 420-06-12	1/4"	2.05"	鉤
<b>直接頭</b>						
<b>Straight</b>						
3/8" x 0.250" (9.5 x 6mm)	PLC 200-06-12	1.68"	PLCD 200-06-12	1/4"	1.82"	迫緊
1/4" (6.4mm) ID	PLC 220-04-12	1.35"	PLCD 220-04-12	1/4"	2.00"	管
3/8" (9.5mm) ID	PLC 220-06-12	1.35"	PLCD 220-06-12	1/4"	1.82"	鉤
1/4" x 3/8" (9.5 x 6mm)	-----		PLCD 220-406-12	1/4"	2.23"	軟管
3/8" x 1/2" (12.7 x 9.5mm)	-----		PLCD 220-608-12	1/4"	2.18"	迫緊
<b>彎頭</b>						
<b>Elbows</b>						
3/8" x 0.250" (9.5 x 6mm)	PLC 210-06-12	1.29"	PLCD 210-06-12	1/4"	1.36"	迫緊
1/4" (6.4mm) ID	PLC 230-04-12	1.22"	PLCD 230-04-12	1/4"	1.36"	管
3/8" (9.5mm) ID	PLC 230-06-12	1.28"	PLCD 230-06-12	1/4"	1.42"	鉤



- ★ 面板固定孔直徑: 11/16".
- ★ 面板厚度: 0.020" min. 1/2" max.
- ★ 面板固定螺帽: 3/4" 六角螺帽.

# EFC-12 9/32" 通徑 P.P. 製

## 規格

- ❖ 工作壓力: 真空至105psi, 7.2 bar
- ❖ 連續使用溫度: 0°C至71°C
- ❖ 可提供符合美國國家衛生基金會NSF C-2規範的接頭

## 應用例

- ❖ 添充管路
- ❖ 排放管路
- ❖ 化學品分注管路

## 材質

- ❖ 本體及閥: P.P.
- ❖ 內彈簧: 316不銹鋼
- ❖ O-Ring: EPDM, 其它材質選用



## 快速接頭母座 Bodies

外牙/管內徑	編號 (附閥)	長度
<b>外牙固定</b>		
1/4" NPT	EFC D 104-12	2.29"
3/8" NPT	EFC D 106-12	2.29"
<b>線上連接</b>		
1/4" (6.4mm) ID	EFC D 174-12	2.23"
3/8" (9.5mm) ID	EFC D 176-12	2.23"
<b>面板固定★</b>		
1/4" (6.4mm) ID	EFC D 164-12	2.23"
3/8" (9.5mm) ID	EFC D 166-12	2.23"



## 快速接頭插 Inserts

螺紋及管內徑	編號 (直通)	編號 (附閥)	長度
<b>管鉤快速接頭插</b>			
1/4" (6.4mm) ID	EFC 224-12	EFC D 224-12	1.33"/1.08"
3/8" (9.5mm) ID	EFC 226-12	EFC D 226-12	1.33"/1.90"
<b>外牙固定快速接頭插</b>			
1/4" NPT	-----	EFC D 244-12	1.77"
3/8" NPT	-----	EFC D 246-12	1.77"
<b>管鉤彎頭 Elbow Hose Barb</b>			
1/4" (6.4mm) ID	EFC 234-12	EFC D 234-12	1.32"/1.45"
3/8" (9.5mm) ID	EFC 236-12	EFC D 236-12	1.32"/1.45"



- ★ 面板固定孔直徑: 0.720"
- ★ 面板厚度: 1.25" max.